


ESD-R-38C-1

Aliases (UECESDR38C1000)

KEMET, ESD-R, EMI Cores, Noise Suppression



Click here for the 3D model.

Dimensions		
D	39mm +/-1.0mm	
D2	17.5mm +/-1.0mm	
Т	14mm +/-1.0mm	

Packaging Specifications	
Packaging	Tray, Box
Packaging Quantity	200
Component Weight	55.5 g

General Information		
Series	ESD-R	
Style	Round - Toroidal	
Cable Type	Round Cable	
Description	EMI Core Solid, For Round Cables, Toroidal Cores With Case	
RoHS	Yes	
SCIP Number	8bc899a4-fad1-46f2-ab35-e2df2597fe4c	
Qualifications	UL94 V-2	
Case Color	White with black tape	
Materials	Ni-Zn	

Specifications	
Temperature Range	-25/+85°C
Effective Frequency	300 MHz (FM Band Range)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.